

Client's ref.: IP00098
Our ref.: 8632-6028us/final/Sue

TITLE

LIQUID CRYSTAL DISPLAY PANEL AND DRIVING METHOD THEREOF

BACKGROUND OF THE INVENTION

Field of the Invention

5 The invention relates to a liquid crystal display (LCD) panel and driving method thereof, more particularly to an LCD panel applying dot inversion driving to obtain video signal polarization arrangement in the form of line inversion, and method of driving the LCD panel.

10 Description of the Related Art

 Fig. 1 is a schematic diagram of an equivalent circuit of a typical thin film transistor liquid crystal display (TFT-LCD). As shown in Fig. 1, crossed data electrodes D1, D2, D3,..., Dy and scan electrodes G1, G2,..., Gx form an LCD
15 panel 1. Each crossed data and scan electrode controls a display unit. For example, crossed data electrode D1 and scan electrode G1 control display unit 100. Display unit 100 or any display unit has an equivalent circuit including a thin film transistor 10 for control, a storage capacitor
20 Cs and a liquid crystal capacitor Clc formed by pixel and common electrodes. Gate and drain of transistor 10 are respectively connected to scan electrode G1 and data electrode D1. Thus, video signal on data electrode D1 is written in display unit 100 through the control of scan
25 signal on scan electrode G1 to transistor 10 on/off. Scan driver 3 sequentially outputs scan signals on every scan electrode G1, G2,..., or Gx, according to scan control

signals, to turn on all transistors in a row of display units and turn off all transistors in other rows at the same time. When the transistors are completely turned on, data driver 2 sends grey levels, with respect to image data to be
5 displayed to the y display units in the on row through data electrodes D1, D2,..., Dy. When x scan lines are completely scanned by scan driver 3 at a time, it displays an image frame on the panel. Accordingly, all scan lines are repeatedly scanned to send video signals for display on the
10 panel frame by frame, thus completing image display.

Video signals on data electrodes D1, D2,..., Dy are generally divided into positive video signals and negative video signals with respect to common electrode voltage VCOM. Additionally, as a driving method for a single display unit
15 in TFT-LCD, positive frames and negative frames respectively receive polarization video signals opposite to each other, such that a liquid crystal molecule will not be biased by only the same polarizing electric field which reduces product lifetime.

20 According to different polarization video signals, common types for a frame arrangement on display units are line inversion and dot inversion.

Fig. 2A is a schematic diagram of video signal polarizations received by display units in the form of line
25 inversion. In Fig. 2A, the left side is an odd frame having video signal polarizations received by display units in a panel area defined by data electrodes Dn-1, Dn, Dn+1 and scan electrodes Gm-1, Gm, Gm+1 in an odd frame, and the right side is an even frame having video signals
30 polarizations received by display units in a panel area

defined by data electrodes D_{n-1} , D_n , D_{n+1} and scan electrodes G_{m-1} , G_m , G_{m+1} . As shown in Fig. 2A, display units in the same row such as G_m receive the same polarization video signals while display units on two
5 adjacent rows such as G_{m-1} and G_{m+1} receive polarization video signals opposite to the row G_m .

Fig. 2B is a schematic diagram of video signal polarizations received by display units in the form of dot inversion. In Fig. 2A, every display unit has a
10 polarization opposite to the surrounding display units. That is, video signals are arranged interlaced with positive and negative polarizations.

Fig. 3 is a schematic diagram of a part of a typical LCD panel circuit. In Fig. 3, the circuit includes data
15 electrodes D_{n-1} , D_n , D_{n+1} , scan electrodes G_{m-1} , G_m , G_{m+1} , and corresponding display units. When scan electrode G_{m-1} receives scan signal, TFTs connected to electrode G_{m-1} are turned on and video signals on data electrodes D_{n-1} , D_n , D_{n+1} are coupled to relative pixel electrodes of display
20 units, respectively. Next, when scan electrode G_m receives scan signal, transistors TFT1, TFT2, TFT3 connected to electrode G_m are turned on and video signals on data electrodes D_{n-1} , D_n , D_{n+1} are coupled to relative pixel electrodes P1, P2, P3 of display units, respectively.

25 When video signal polarizations are arranged in dot inversion, electric field distribution between adjacent pixels as is shown in Fig. 4A. When video signal polarizations are arranged in line inversion, electric field distribution between adjacent pixels as is shown in Fig. 4B.
30 In Fig. 4A and 4B, numbers 40, 42 indicate front and rear

substrates of an LCD panel, symbol Bx indicates black matrix, symbol E_Vcom indicates common electrode, Dn, Dn+1 indicate data electrodes, and P1~P3 indicate pixel electrodes. It is noted that arrows between substrates 40
5 and 42 indicate electric field distribution.

As shown in Fig. 4A, during dot inversion driving, edges between adjacent pixels (such as an interface of P1 and P2 and another interface of P2 and P3) present deformed electrical lines. These deformed lines cause light leakage
10 on a display frame. Therefore, black matrix covers leak areas for a higher display quality. However, the used areas for black matrix will decrease transmittance because area available for pixels is reduced.

As shown in Fig. 4B, during line inversion driving,
15 every two adjacent pixels in the same row have the same polarization (such as "+"). Therefore, edges between adjacent pixels (such as an interface of P1 and P2 and another interface of P2 and P3) present less deformed electric field compared with Fig. 4A. The required area of
20 black matrix in this design is lower and relatively the available area for pixels is increased. Hence, the panel transmittance is increased. However, during line inversion driving, the coupling between data bus and pixel and common electrodes easily causes crosstalk on a display frame.

25 SUMMARY OF THE INVENTION

It is an object of the present invention to provide an LCD panel and driving method thereof, which uses dot inversion driving to present a video signal polarization arrangement spatially similar to line inversion driving on

the panel. Thus, the required area of black matrix is reduced, thus increasing transmittance of the panel and reducing crosstalk.

The present invention provides an LCD panel, including
5 a plurality of scan electrodes, a plurality of data electrodes, and a plurality of display units. Each display unit corresponds to crossed scan and data electrodes and has a pixel electrode and a control transistor. Gates of control transistors of two adjacent display units in a row
10 between first and second adjacent scan electrodes are respectively connected to the first scan electrode and the second scan electrode.

Gates of control transistors of two adjacent display units in a column between two adjacent data electrodes are
15 not connected to the same scan electrode.

The LCD panel also includes a common electrode. The common electrode is connected to each pixel electrode to form a liquid crystal capacitor for each display unit.

According to the object of the invention, a driving
20 method for LCD panel includes changing display unit arrangement in an LCD panel such that gates of control transistors of two adjacent display units in the same row are respectively connected to a first scan electrode and a second scan electrode, thus forming a desired LCD panel
25 structure, and performing dot inversion driving to the display units. Therefore, when dot inversion driving is completed for a frame on the LCD panel, all display units in the same row of the frame have the same video signal polarization and display units in two adjacent rows of the
30 frame present polarization opposite to each other.

DESCRIPTION OF THE DRAWINGS

The present invention will be described by way of exemplary embodiments, but not limitations, illustrated in the accompanying drawings in which like references denote
5 similar elements, and in which:

Fig. 1 is a schematic diagram of an equivalent circuit of a typical thin film transistor liquid crystal display (TFT-LCD);

Fig. 2A is a schematic diagram of video signal
10 polarizations received by display units in the form of line inversion;

Fig. 2B is a schematic diagram of video signal polarizations received by display units in the form of dot inversion;

15 Fig. 3 is a schematic diagram of a part of a typical LCD panel circuit;

Fig. 4A is a schematic diagram of electric field distribution between adjacent pixels when video signal polarizations are arranged in dot inversion;

20 Fig. 4B is a schematic diagram of electric field distribution between adjacent pixels when video signal polarizations are arranged in line inversion;

Fig. 5 is a schematic diagram of a liquid crystal display (LCD) panel according to the invention;

25 Fig. 6 is a schematic diagram of a partial frame of Fig. 5 according to the invention; and

Figs. 7A~7D are schematic diagrams of video signal polarization arrangement for every pixel electrode in a

frame when scan signals are sequentially sent to scan electrodes Gx-1~Gx+1 in dot inversion.

DETAILED DESCRIPTION OF THE INVENTION

Fig. 5 is a schematic diagram of a liquid crystal display (LCD) panel according to the invention.

The inventive driving method for LCD panel majorly changes the coupling arrangement of display units for the LCD panel, such that gates of control transistors of two adjacent display units in the same row are connected to a first scan electrode and a second scan electrode, respectively, and thus obtain the LCD panel structure shown in Fig. 5. Next, dot inversion driving is used on the display units of the panel. As such, when dot inversion driving is completed for a frame on the LCD panel, all display units in the same row of the frame have the same video signal polarization and display units in two adjacent rows of the frame present polarization opposite to each other.

Referring to Fig. 5 now, the LCD panel includes a plurality of scan electrodes (G1, G2,..., Gm-1, Gm), a plurality of data electrodes (D1, D2, D3,..., Dn-1, Dn), a plurality of display units, and a common electrode Vcom. Each display unit corresponds to a crossed scan and data electrode and has a pixel electrode Px and a control transistor Tx. Gates of control transistors of two adjacent display units in a row between first and second adjacent scan electrodes are respectively connected to the first scan electrode and the second scan electrode. The common electrode is connected to each pixel electrode to form a

relative liquid crystal capacitor C_{lc} and storage capacitor C_s of each display unit 50.

The feature of the inventive panel structure is that gates of control transistors of two adjacent display units in a row between first and second adjacent scan electrodes are respectively connected to the first scan electrode and the second scan electrode, and gates of control transistors of two adjacent display units in a column between two adjacent data electrodes are not connected to the same scan electrode. For example, gate G2 of control transistor Tx1 of display unit P1 is connected to scan electrode G2, and gate G3 of control transistor Tx2 of display unit P2 is connected to scan electrode G3.

Referring to Fig. 5 again, an example is given by scan electrodes G2, G3, where a row of display units P1, P2, P3,..., Pn-1, Pn are arranged between G2 and G3. Gate of control transistor Tx1 of display unit P1 is connected to scan electrode G1. Gate of control transistor Tx2 of display unit P2 is connected to scan electrode G3. Gate of control transistor Tx3 of display unit P3 is connected to scan electrode G2. Gate of control transistor Txn-1 of display unit Pn-1 is connected to scan electrode G3. Gate of control transistor Txn of display unit Pn is connected to scan electrode G2. In such an arrangement, gates of control transistors of any two adjacent display units in the display units P1~Pn are respectively connected to scan electrodes G2 (first scan electrode) and G3 (second electrode).

Fig. 6 is a schematic diagram of a partial frame of Fig. 5 according to the invention. The partial frame includes data electrodes Dy-1, Dy, Dy+1, scan electrodes Gx-

1, Gx, Gx+1 and control transistors M1~M9 and pixel electrodes Px1~Px9 corresponding to display units. Figs. 7A~7D are schematic diagrams of video signal polarization arrangement for every pixel electrode in a frame when scan signals are sequentially sent to scan electrodes Gx-1~Gx+1 in dot inversion. The following description using dot inversion obtaining line inversion arrangement on a frame of the inventive LCD panel is given by reference to Figs. 6, 7A~7D.

10 At the beginning, the panel is driven by dot inversion.

When scan signal is sent to scan electrode Gx-1, TFTs M1~M3 are turned on. Data electrodes Dy-1, Dy, Dy+1 then output video signals (whose polarizations are "+", "-", "+", respectively) respectively coupled to pixel electrodes Px1~Px3. The resulting video signal polarization arrangement on the frame is shown in Fig. 7A.

Next, when scan signal is sent to scan electrode Gx, TFTs M4~M6 are turned on. Data electrodes Dy-1, Dy, Dy+1 then output video signals (whose polarizations are "-", "+", "-", respectively) respectively coupled to pixel electrodes Px4~Px6. The resulting video signal polarization arrangement on the frame is shown in Fig. 7B.

Next, when scan signal is sent to scan electrode Gx+1, TFTs M7~M9 are turned on. Data electrodes Dy-1, Dy, Dy+1 then output video signals (whose polarizations are "+", "-", "+", respectively) respectively coupled to pixel electrodes Px7~Px9. The resulting video signal polarization arrangement on the frame is shown in Fig. 7C.

Next, when scan signal is sequentially sent to scan electrode Gx+2 (not shown), TFTs with respect to Gx+2 are

turned on. Data electrodes Dy-1, Dy, Dy+1 then output video signals (whose polarizations are "-", "+", "-", respectively) respectively coupled to corresponding pixel electrodes. The resulting video signal polarization arrangement on the frame is shown in Fig. 7D, where symbols "+" and "-" in dotted line indicate currently written video signal polarizations.

As shown in Fig. 7D, the resulting video signal polarization arrangement on pixel electrodes Px1-Px9 in the frame presents a line inversion polarization arrangement. Therefore, as shown in Fig. 4B, edges between two adjacent pixels have less electric field deformation than in Fig. 4A. Accordingly, black matrix Bx area is reduced by design and the relative area available for pixels is increased, thereby increasing transmittance of the panel.

In addition, due to the use of dot inversion driving, positive polarization and negative polarization on data bus are respectively halved, thus the coupling between data bus and a pixel electrode Px and common electrode Vcom does not generate crosstalk from positive and negative polarization cancellation.

Thus, the invention provides a novel LCD panel structure, applying dot inversion driving to obtain a polarization arrangement spatially similar to line inversion driving. Thus, black matrix area is reduced such that the panel transmittance is increased while crosstalk is reduced.

While the invention has been described by way of example and in terms of the preferred embodiments, it is to be understood that the invention is not limited to the disclosed embodiments. To the contrary, it is intended to

Client's ref.: IP00098
Our ref.: 0602-6028us/final/Sue

cover various modifications and similar arrangements (as
would be apparent to those skilled in the art). Therefore,
the scope of the appended claims should be accorded the
broadest interpretation so as to encompass all such
5 modifications and similar arrangements.